

# G493-SB2-AAP1

## GPU Server - 4U DP 8-GPU 12-bay NVMe/SATA



### Features

- Supports up to 8 x double slot Gen5 GPU cards
- 4th Gen. Intel® Xeon® Scalable Processors
- Intel® Xeon® CPU Max Series
- Dual processor, LGA4677
- 8-Channel RDIMM DDR5, 32 x DIMMs
- Dual ROM Architecture supported
- 2 x 10Gb/s BASE-T LAN ports (Intel® X710-AT2)
- 1 x dedicated management port
- 12 x 3.5/2.5" NVMe/SATA hot-swappable bays
- 1 x Ultra-Fast M.2 with PCIe Gen3 interface
- 4 x FHHL PCIe Gen5 x16 slots on rear side
- 2 x LP PCIe Gen5 x16 MD2 expansion slots on front side
- 3+1 3000W (240V) 80 PLUS Titanium redundant power supply

### Specification

<b>Dimensions</b>	4U (W448 x H176 x D880 mm)	<b>Rear I/O</b>	N/A
<b>Motherboard</b>	MSB3-G40	<b>Backplane I/O</b>	PCIe Gen5 x4 or SATA 6Gb/s or SAS 12Gb/s
<b>CPU</b>	4th Gen Intel® Xeon® Scalable Processors Intel® Xeon® CPU Max Series Intel® Xeon® Platinum Processor, Intel® Xeon® Gold Processor, Intel® Xeon® Silver Processor CPU TDP up to 350W	<b>TPM</b>	1 x TPM header with SPI interface Optional TPM2.0 kit: CTM010
<b>Socket</b>	2 x LGA 4677 (Socket E)	<b>Power Supply</b>	3+1 3000W (240V) 80 PLUS Titanium redundant power supply AC Input: 110-240V
<b>Chipset</b>	Intel® C741 Chipset	<b>System Management</b>	Aspeed® AST2600 management controller GIGABYTE Management Console (AMI MegaRAC SP-X)
<b>Memory</b>	8-Channel DDR5 memory, 32 x DIMM slots RDIMM modules up to 128GB supported 3DS RDIMM modules up to 256GB supported Memory speed: Up to 4800 MHz (1DPC), 4400 MHz (2DPC)	<b>OS Compatibility</b>	Windows Server 2019 / 2022 RHEL 8.4 / 8.5 / 8.6 / 8.7 / 9.0 / 9.1 (x64) SLES 15 SP3 / 15 SP4 (x64) Ubuntu 22.04 LTS / 22.04.1 LTS (x64) VMware ESXi 7.0 Update 3i / 8.0
<b>LAN</b>	2 x 10Gb/s BASE-T LAN ports (Intel® X710-AT2) Supported NCSI function 1 x 10/100/1000 management LAN	<b>System Fans</b>	6 x 60x60x38mm (23,000rpm)
<b>Video</b>	Integrated in Aspeed AST2600 2D Video Graphic Adapter with PCIe bus interface 1920x1200@60Hz 32bpp, DDR4 SDRAM	<b>Operating Properties</b>	Operating temperature: 10°C to 35°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
<b>Storage</b>	12 x 3.5" SATA/SAS hot-swappable bays SAS card is required for SAS devices support	<b>Packaging Content</b>	1 x G493-SB2, 2 x CPU heatsinks, 6 x Carrier clips, 1 x Rail kit
<b>RAID</b>	Intel SATA RAID 0/1/10/5	<b>Reference Numbers</b>	Barebone package: 6NG493SB2DR000AAP1* - Motherboard: 9MSB3G40NR-000 - Rail kit: 25HB2-A96100-K0R - CPU Fan-sink: 25ST1-363204-C1R - Back plane board_12-port_3.5": 9CBP20C7NR-00 - Power supply: 25EPO-230005-G1S - C19 power cord 125V/15A (US): 25CP1-018000-Q0R (optional) - C19 power cord 250V/16A (EU): 25CP3-01830H-Q0R (optional)
<b>Expansion Slots</b>	8 x PCIe Gen5 x16 FHFL slots for GPUs on rear side 4 x PCIe Gen5 x16 FHFL slots on rear side 2 x PCIe Gen5 x16 Low-profile MD2 slots on front side 1 x M.2 slot (M-key, PCIe Gen3 x1, supports 2280/22110)		
<b>Front I/O</b>	2 x USB 3.2 Gen1, 1 x VGA, 2 x RJ45, 1 x MLAN		



Learn more about GIGABYTE server, visit <https://www.gigacomputing.com>

- \* All specifications are subject to change without notice. Please visit our website for the latest information.
- \* Intel, the Intel logo, Xeon, and other Intel marks are trademarks of Intel Corporation or its subsidiaries.
- \* All other brands, logos and names are property of their respective owners.

© 2023 Giga Computing Technology Co., Ltd. All rights reserved.

Engineered by

