


R182-NA1

Intel Xeon Rack Server - 1U DP 10-Bay Gen4 NVMe



Features

- 3rd Gen. Intel® Xeon® Scalable Processors
- 8-Channel RDIMM/LRDIMM DDR4 per processor, 32 x DIMMs
- Dual ROM technology supported
- 2 x 1Gb/s LAN ports (Intel® I350-AM2)
- 1 x Dedicated management port
- 10 x 2.5" SATA/Gen4 NVMe hot-swappable HDD/SSD bays
- 2 x 7-pin SATA DOM supported
- 2 x PCIe Gen4 x16 expansion slots
- 1 x OCP 3.0 Gen4 x16 mezzanine slot
- 1 x OCP 2.0 Gen3 x8 mezzanine slot
- 1300W (240V) 80 PLUS Platinum redundant power supply

Specification

Dimensions	1U (438 x 43.5 x 730 mm)	Backplane I/O	10 x 2.5" SATA/SAS/NVMe hybrid ports Bandwidth: PCIe Gen4 x4 or SATA 6Gb/s or SAS 12Gb/s
Motherboard	MR92-FS1	TPM	1 x TPM header with SPI interface (Optional TPM2.0 kit: CTM010)
CPU	3rd Gen Intel® Xeon® Scalable Processors 10nm technology, CPU TDP up to 270W 2 x LGA 4189 sockets (Socket P+)	Power Supply	1+1 1300W 80 PLUS Platinum redundant power supply AC Input: 100-240V
Chipset	Intel® C621A Express Chipset	System Management	Aspeed® AST2600 management controller GIGABYTE Management Console (AMI MegaRAC SP-X)
Memory	8-Channel DDR4 memory, 32 x DIMM slots RDIMM/LRDIMM modules up to 128GB supported 3DS RDIMM/LRDIMM modules up to 256GB supported 1.2V modules: 3200/2933/2666 MHz	OS Compatibility	Windows Server 2016 / 2019 RHEL 8.2 (x64) / 8.3 (x64) or later Red Hat OpenStack Platform 16 SLES 12 SP5 (x64) / 15 SP2 (x64) or later Ubuntu 20.04 LTS (x64) / 20.04.1 LTS (x64) or later VMware ESXi 6.7 Update3 P03 / 7.0 Update2 Citrix Hypervisor 8.2.0
LAN	2 x 1GbE LAN ports (1 x Intel® I350-AM2) 1 x 10/100/1000 management LAN	System Fans	8 x 40x40x56mm (29,700rpm)
Video	Integrated in Aspeed AST2600 2D Video Graphic Adapter with PCIe bus interface 1920x1200@60Hz 32bpp, DDR4 SDRAM	Operating Properties	Operating temperature: 10°C to 35°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
Storage	10 x 2.5" SATA/Gen4 NVMe hot-swap HDD/SSD bays SAS card is required for SAS devices support	Packaging Content	1 x R182-NA1, 2 x CPU heatsinks, 1 x Rail kit
RAID	RAID Level depends on SAS HBA	Reference Numbers	Barebone package: 6NR182NA1MR-00 - Motherboard: 9MR92FS1NR-00 - Rail kit: 25HB2-3A0203-K0R - CPU heatsink: 25ST1-453204-M1R - Power supply: 25EP0-213002-F3S
Expansion Slots	2 x PCIe x16 slots (Gen4 x16), FHHL 1 x OCP 3.0 mezzanine slot (Gen4 x16) - Supported NCSI 1 x OCP 2.0 mezzanine slot (Gen3 x8) - Supported NCSI		
Front I/O	1 x USB 3.0		
Rear I/O	2 x USB 3.0, 1 x VGA, 2 x RJ45, 1 x MLAN		



Learn more about GIGABYTE server solutions, visit www.gigabyte.com/Enterprise

* All specifications are subject to change without notice. Please visit our website for the latest information.

* Intel, the Intel logo, Xeon, and other Intel marks are trademarks of Intel Corporation or its subsidiaries.

* All other brands, logos and names are property of their respective owners.

© 2021 GIGABYTE Technology Co., Ltd. All rights reserved.